



# 6" Seam Tape

Double-Stick Elastomeric Tape

### PRODUCT OVERVIEW

Seam Tape is a double-stick elastomeric tape designed for use with NAC sheet applied or liquid applied membrane systems.

Seam Tape seals and waterproofs seams, joints, shower curbs, drains, exterior decks and balconies and other protrusions. It can be used in interior and exterior applications and requires the use of an appropriate NAC primer.

Seam Tape is NOT a stand alone product and where exposed, must be covered with membrane.

### FEATURES & BENEFITS

- Suitable for interior and exterior use
- Secures edge seams for a water-tight seal
- Appropriate for thin or thick-bed applications
- Tile can be installed same day as membrane if no flood testing is required
- Excellent companion product for the Extreme Waterproofing systems

### INSTALLATION

- Apply the appropriate NAC primer to the area where the Seam Tape and membrane will be installed
- Cut Seam Tape to desired length and position with the white release paper facing down and the membrane overlapping Seam Tape by 3"
- Remove white release paper from the underside and apply Seam Tape to the area that was primed
- Use flat side of trowel to press Seam Tape into place
- Allow first membrane sheet to overlap Seam Tape by 3"
- Start second membrane sheet over the remaining 3" of tape and butt-jointed next to the first sheet. DO NOT overlap membrane sheets
- Remove protective film from the top of the Seam Tape and press membrane into Seam Tape
- Use flat side of trowel or 75-100# roller to finish membrane installation
- For floor to wall installation, flash Seam Tape up wall 3" leaving 3" of Seam Tape on the floor.

### INSTALLATION cont.



Image 1: Floor Installation butt-joint membrane seams



Image 2: Floor to wall edge seam



Image 3: Edge Seam

Please refer to the individual membrane instructions for complete installation

#### Primer Reference Chart

NAC	Interior Application			Exterior Application		
	Below Grade	On Grade	Above Grade	Below Grade	On Grade	Above Grade
NAC TAC	✓	✓	✓	✓	✓	✓
NAC TAC II		✓	✓			
NS97				✓	✓	✓

For complete information about primers, refer to the Primer PDS



National Applied Construction Products, Inc.

3200 South Main St. Akron, OH 44319

www.NACproducts.com

800.633.4622 • fax: 330.644.3557

©2020 NAC Products, Inc. All Rights Reserved Rev. 6/20